



TECHNICAL DATA SHEET – PLOTTER VINYLs

SUPTAC S5000

2.56-mil (0.065-mm), high performance, calendered, polymeric PVC film, which is coated with a pressure-sensitive, solvent-based, acrylic adhesive.

FILM FEATURES:

	<u>Indicative value</u>	
• Thickness:	2.56 mil 0.065 mm	
	<u>Average values</u>	<u>Standard</u>
• Tensile strength:	min. 7.74 lb./in. min. 35 N/25mm	HEXNFX4102I
• Elongation at break:	min. 100 %	HEXNFX4102I
• Shrinkage 168 hours at 158 °F (70 °C):	< 0.015 inch < 0.4 mm	HEXRET00I

LINER:

- 92# silicone-coated Kraft paper with grey print.
- Stable under hygrometric variations.

ADHESIVE PROPERTIES:

	<u>Average values</u>	<u>Standard</u>
180° peel strength test on glass:		
after 20 minutes of application	3.098 lb./in. 14 N/25mm	HEXFTM00I
after 24 hours of application	3.98 lb./in. 18 N/25mm	
Initial tack	3.32 lb./in. 15 N/25mm	HEXFTM009
Release	0.066 lb./in. 0.3 N/25mm	HEXFTM003

- Resistance to solvents: the adhesive is resistant to most chemicals (alcohol, petrol, diluted acids, oils, fuels).

ADHESIVE:

- Colorless solvent-based acrylic adhesive (white for S5136B).
- Immediate and permanent adhesion, suitable for wet application to flat surfaces only.

USER'S INSTRUCTIONS:

- Recommended minimum application temperature: +44 °F (+7 °C).
- Operating temperature range: -40 °F to +194 °F (-40 °C to +90 °C).
- Adhesion to glass, steel, aluminum, PVC, melamine, etc. except grain substrates or substrates coated with acrylic paint.
- In the case of already painted substrate, self-adhesive media must only be applied to undamaged original paintwork. If the paintwork is not original and/or damaged, the application and the removal are at the judgement and risk of the installer.

OPERATING RECOMMENDATIONS:

- For more information on the application method of the SUPTAC film, please refer to the Application Guide on the "Professionals" pages, category "Plotter vinyls" on our website www.hexis-graphics.com.

STORAGE:

- Shelf life (before application):

The shelf life of this film is 2 years when stored unopened in its original packaging at a temperature ranging from +59 °F to +77 °F (+15 °C to +25 °C) with relative humidity between 30 % and 70 %.

INDICATIVE DURABILITIES:

- Vertical outdoor exposure:

Dominant color	Max. indicative durability (years) ⁽¹⁾
White, glossy black	10
Colors, other tints	8
Metallic colors	4
S5NORB Nordic Blue, S5ELEB Electric Blue, S5GBEB Beige Grey	2

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application.

The measuring methods for the standards quoted above served as basis for the development of our own measuring methods which are available on request. Please feel free to contact us to get the latest instructions in use.

All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.