



#### TECHNICAL DATA SHEET - DOUBLE-SIDED TAPE

### DOUBLE-SIDED

A 38-µm double sided adhesive tape composed of a nonwoven fabric substrate and a transparent rubber adhesive, which is pressure-sensitive. Intended for permanently fixing lightweight objects onto various substrates. Indoor application.

# **FILM FEATURES:**

#### Average values

Total thickness of the product (µm): 100
Thickness of tape + adhesive (µm): 38
Weight of the adhesive (g/m²): 90

## LINER:

• A 65-µm double-sided silicone-coated paper.

#### **ADHESIVE PROPERTIES:**

#### Average values

Peel strength test (N/cm):

#### **ADHESIVE:**

Transparent synthetic rubber adhesive, which is pressure-sensitive.

#### **USER'S INSTRUCTIONS:**

- Recommended minimum application temperature: +15 °C to +25 °C (+59 °F to +77 °F).
- Removal is easy and residue-free.
- In the case of already painted substrate, self-adhesive media must only be applied onto undamaged original paintwork. If the paintwork is not original and/or damaged, the application and the removal are at the judgement and risk of the installer.

### **STORAGE:**

Shelf life (before application):

The shelf life of this film is I year when stored unopened in its original packaging at a temperature ranging from +15 °C and +25 °C (+59 °F to +77 °F) with relative humidity between 30 % and 70 %.

#### **NOTES:**

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. The measuring methods for the standards quoted above served as basis for the development of our own measuring methods which are available on request. Please feel free to contact us to get the latest instructions in use.

All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.