



## AG300

### PRODUCT DESCRIPTION:

Conformable film composed of a 38- $\mu$ m ETFE, which is coated with a pressure-sensitive adhesive. The film is easy to clean and can be used as anti-graffiti protection. The film is suitable for cold-laminating HEXIS digital printing films, which have been printed with solvent, eco-solvent and latex inks. Its mechanical properties allow it to be applied to slightly curved or slightly complex surfaces without losing its anti-graffiti features. Glossy surface finish.

### FILM FEATURES:

• Thickness	(Indicative value) <b>38 <math>\mu</math>m</b>	
• Tensile strength	(Average values) <b>&gt; 20 N/25 mm</b>	Method <b>HEXNFX41021</b>
• Elongation at break	(Average values) <b>&gt; 100 %</b>	Method <b>HEXNFX41021</b>
• Shrinkage 168 hours at 70 °C (158 °F)	(Average values) <b>&lt; 0.2 mm</b>	Method <b>HEXRET001</b>

### LINER:

- 75- $\mu$ m, silicone-coated PET liner.

### ADHESIVE PROPERTIES:

(Measured average values at publication of the technical data sheet)

• Peel strength test at 180°; Measurement support glass		
after 20 minutes of application	(Average values) <b>10 N/25 mm</b>	Method <b>HEXFMT001</b>
after 24 hours of application	(Average values) <b>12 N/25 mm</b>	Method <b>HEXFMT001</b>
• Initial tack	(Average values) <b>17 N/25 mm</b>	Method <b>HEXFMT009</b>
• Release	(Average values) <b>0.1 N/25 mm</b>	Method <b>HEXFMT003</b>

### ADHESIVE:

- Solvent-based acrylic adhesive.
- Immediate and permanent adhesion.

### USER'S INSTRUCTIONS:

- Dry application method
- Recommended minimum application temperature: +10 °C (+50 °F)
- Operating temperature range: -40 °C to +90 °C (-40 °F to +194 °F)
- Anti-graffiti protection of HEXIS digital printing films.
- This film is moreover perfectly suitable for application by overlapping and can also be covered with adhesive-coated film.
- To clean the film, use a non-abrasive sponge or soft cloth with acetone, alcohol, soapy water or HEX'AG.
- In the case of an already painted substrate, self-adhesive media must only be applied to undamaged original paintwork. If the paintwork is not original and/or damaged, the application and the removal are at the judgement and risk of the installer.



## OPERATING RECOMMENDATIONS:

- Optimal drying time for the inks before laminating, coating or further processing of a HEXIS digital printing film, which has been printed with solvent, eco-solvent and latex inks, is:
  - 48 hours for a cast film;
  - 24 hours for a calendered film.

## STORAGE:



Storage period before use  
**2 years**



Storage temperature  
**+15 °C to +25 °C (+59 °F to +77 °F)**



Relative humidity during storage  
**with relative humidity of 50 %**



Storage area  
**in a dust-free environment**



Storage method before use  
**in its original packaging**



Orientation of rolls before use  
**horizontally**

## DURABILITY: (Central European climate)

- Vertical outdoor exposure:
  - Graffiti-free, not cleaned using solvents: **8 years.**
  - Cleaned film: dependent on the method and frequency of the cleaning.

*To find the indicative durabilities of the films for any other exposure and geographical area, please refer to the «Conversion rules for indicative durabilities according to geographical area» chart available under Durability, on the «Professionals» pages on our site [www.hexis-graphics.com](http://www.hexis-graphics.com).*

## NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. The measuring methods for the standards quoted above served as the basis for the development of our own measuring methods, which are available on request. Please feel free to contact us to get the latest instructions in use. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).