

# BFSHIELD



## PRODUCT DESCRIPTION:

*BFSHIELD* is a transparent, self-healing, adhesive-coated film that was specially developed for protecting vehicle windscreens against impacts and scratches. Due to its self-healing properties at room temperature, stone chips and micro-scratches caused by windscreen wipers, for example, disappear instantly. Excellent water evacuation due to its water-repellent surface. Application to the exterior of windshields.

## FILM FEATURES:

- Total thickness (film + adhesive) (Indicative value)  
**180 µm (7.1 mil) ±10 %**
- Visible light transmission (Indicative value)  
**» 90**
- Max. UV transmission (Indicative value)  
**« 1**

## LINER:

- Polyester film with silicone-coated adhesive.
- Silicone-coated polyester liner.

## ADHESIVE PROPERTIES:

- Measurement support glass (Average values) Method
- Peel strength test after 24 hours of application **6 N/25 mm** **HEXFTM001**

## ADHESIVE:

- Acrylic adhesive.

## USER'S INSTRUCTIONS:

- Recommended minimum application temperature: +18 °C (+64 °F)
- Operating temperature range: -40 °C to +90 °C (-40 °F to +194 °F)
- For an optimal installation of the BFSHIELD film without any visual distortion, the film application must be carried out by an installer who has followed the BODYFENCE and/or TEAR-OFF training provided by HEXIS S.A.S.
- When handling the film - excluding film application - always touch BFSHIELD with clean, dry hands.
- The film must be applied without thermoforming.
- Cut the film to the size of the part to be wrapped, allowing +10 cm (4 in.) of extra margin.

*The remaining film must be stored on its original core (do not cut the rolls into several lengths or widths, do not repackage the product); the roll must be properly closed immediately after use (masking tape or roll-collars) in order to preserve all its qualities.*

*Caution: BFSHIELD is equipped with a protective surface film, which must be removed in the timeframe between positioning the adhesive-coated film on the windscreen and applying it.*

- Position and apply the film performing the wet application method using the diluted HEXISOAP solution (press once on the dispenser bottle per litre of water for correct dosing).

*During the removal of the adhesive protection liner, the diluted HEXISOAP must be sprayed.*

- Only use the special tools dedicated to the application of vehicle window films.

*If you notice a certain resistance on the film surface when squeegeeing during application, pour a mixture of HEXISOAP solution diluted with water into the sprayer (press once on the dispenser bottle per litre of water for correct dosing) and spray the BFSHIELD surface with this installation liquid.*

- The adhesion is nearly instantaneous: do not peel off the film once applied.

*The film continues to conform to the glass after application, reaching its maximum transparency after a few days.*

- Clean the wiper blades regularly and replace them at the first signs of wear.
- Use the wipers exclusively on wet windscreens.
- If there is frost on the surface of the film, use a de-icing liquid such as 'AERO DE-ICER' by HOLTS®. Do not use abrasive tools such as snow brushes, ice scrapers, etc. or sharp accessories (metallic blades of window scrapers) on the surface of the film, as this could cause serious damage.

### OPERATING RECOMMENDATIONS:

*Caution: Please enquire about the current legislation in the country of use of the said film prior to any modification of the vehicle's glazing. HEXIS cannot be held liable for any non-compliance with the current legislation of the country of use.*

- The film can be cleaned with soapy water or glass cleaner and a non-abrasive sponge in the case of contaminants such as dust, mud, bird droppings, traces of dirty liquids, insects, etc.
- Dry the film with a rubber squeegee or a clean microfibre cloth.

*To extend the lifespan of BFSHIELD and regenerate the hydrophobic and self-healing properties of the film, HEXIS recommend that you regularly apply the product NANOSERUM by HEXIS to the surface of the film. The film may require a monthly treatment in the event of prolonged use of the windscreen wipers.*

### STORAGE:



Storage period before use  
**1 year**



Storage temperature  
**between +18 °C to +22 °C (+64 °F to +72 °F)**



Relative humidity during storage  
**with relative humidity between 40 % and 60 %**



Storage area  
**The packaging must be stored on a dry, completely flat and uniform surface.**



Storage method before use  
**in its original packaging**



Orientation of rolls before use  
**horizontally**

### DURABILITY: CENTRAL EUROPEAN CLIMATE

- Vertical exposure:  
Up to 1 year (under normal road use conditions).
- Lifespan depends on the type and preparation of substrate, exposure conditions as well as nature and frequency of the cleaning.

### NOTES:

Due to the wide variety of existing glazings and the constant evolution of materials, it is the responsibility of the user to verify, for each application, the correct match of the product with the substrate. In case of doubt, a qualified professional should be consulted to check that the glass is compatible with the film. The published information is provided for information purposes only and is based on measurements regularly performed in the laboratory. They do not constitute an absolute guarantee of the product's performance. The seller accepts no liability for indirect damages, and its liability is in all cases limited to the price of the products in question. All our technical specifications are subject to change without notice. Updates are automatically available on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).