



DOUBLE FACE

PRODUCT DESCRIPTION:

A 38- μ m double sided adhesive tape composed of a nonwoven fabric substrate and a transparent rubber adhesive, which is pressure-sensitive. Intended for permanently fixing lightweight objects onto various substrates. Indoor application.

FILM FEATURES:

- Total thickness (Average values)
100 μ m
- Total thickness (film + adhesive) (Average values)
38 μ m
- Total weight (Average values)
90 g/m²

LINER:

- 65- μ m, double-sided, silicone-coated paper.

ADHESIVE PROPERTIES:

Film's adhesion (Average values)
10 N/cm

ADHESIVE:

- Transparent, pressure-sensitive, synthetic rubber adhesive.

USER'S INSTRUCTIONS:

- Recommended minimum application temperature: +15 °C to +25 °C (+59 °F to +77 °F)
- Removal is easy and residue-free.
- In the case of an already painted substrate, apply to undamaged original paintwork only. If the paintwork is not original and/or damaged, the application and the removal are at the judgement and risk of the installer.

STORAGE:



Storage period before use
1 year



Relative humidity during storage
with relative humidity between 30 % and 70 %



Storage temperature
+15 °C to +25 °C (+59 °F to +77 °F)



Storage method before use
in its unopened original packaging

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.