



## P135



### PRODUCT DESCRIPTION:

A 150-µm paper for solvent, eco-solvent, UV and latex inkjet printing. Satin surface finish.

### FILM FEATURES:

• Total thickness	(Indicative value) <b>150 µm</b>
• Total weight	(Indicative value) <b>135 g/m<sup>2</sup></b>
• Opacity	(Indicative value) <b>&gt; 97 %</b>

### PRINTING GUIDE:

- Comply with the conditions of storage temperature and hygometry before printing.
- Use the HEXIS ICC profiles, available on our website [www.hexis-graphics.com](http://www.hexis-graphics.com), to perform high quality work while optimising the ink quantity required for this substrate.
- Touch-dry after less than 5 minutes depending on printer used.
- Optimal drying time for the inks before laminating, coating or further processing is 24 hours.

### OPERATING RECOMMENDATIONS:

- The surface finish of your printings may be modified/improved/protected by applying the appropriate laminate: V650 or V700 (matt, satin or glossy).

### STORAGE:



Storage period before use  
**1 year**



Relative humidity during storage  
**with relative humidity between 30 % and 65 %**



Storage temperature  
**+10 °C to +30 °C (+50 °F to +86 °F)**



Storage method before use  
**in its unopened original packaging**

### NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).