



# P210



## PRODUCT DESCRIPTION:

A 230-µm photo paper, for solvent, eco-solvent, UV and latex inkjet printing. Glossy surface finish.

## FILM FEATURES:

- Total thickness (Average values)  
**230 µm**
- Total weight of the product (without liner) (Average values)  
**210 g/m<sup>2</sup>**
- Opacity (Average values)  
**> 98 %**

## PRINTING GUIDE:

- Use the HEXIS ICC profiles, available on our website [www.hexis-graphics.com](http://www.hexis-graphics.com), to perform high quality work while optimising the ink quantity required for this substrate.
- Comply with the conditions of storage temperature and hygometry before printing.
- Touch-dry after less than 5 minutes depending on printer used.
- Optimal drying time for the inks before laminating, coating or further processing is 24 hours.

## USER'S INSTRUCTIONS:

*Water- and weather-proof paper.*

## OPERATING RECOMMENDATIONS:

- The surface finish of your printings may be modified/improved/protected by applying the appropriate laminate: V650 or V700 (matt, satin or glossy).

*It is recommended to laminate the P210 film for any long-term outdoor exposure or if it is subject to severe climate conditions.*

## STORAGE:



Storage period before use  
**1 year**



Relative humidity during storage  
**with relative humidity between 30 % and 65 %**



Storage temperature  
**+10 °C to +30 °C (+50 °F to +86 °F)**



Storage method before use  
**in its unopened original packaging**

## NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).