

# **TECHNICAL DATA SHEET**





# PAP120JF









# **PRODUCT DESCRIPTION:**

Fluorescent yellow, non-adhesive, 120-g/m² printable paper.

### **FILM FEATURES:**

· Thickness

(Indicative value)
124 µm

Weight

(Indicative value)
120 g/m²

#### **PRINTING GUIDE:**

· Store under printing conditions (temperature, hygrometry) a few days before printing.

#### **USER'S INSTRUCTIONS:**

· For indoor use.

#### STORAGE:



Storage period before use

1 year



Storage temperature

+15 °C to +25 °C (+59 °F to +77 °F)



Relative humidity during storage

with relative humidity of 50 %



Storage area

in a dust-free environment



Storage method before use in its original packaging



Orientation of rolls before use **vertically** 



Roll storage method after use

In the case of partial use, replace the remaining roll in its original packaging.

## NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.