

# **TECHNICAL DATA SHEET**





# PAP132DB









## **PRODUCT DESCRIPTION:**

Coated multilayer paper, 130 g/m², with blue back. For solvent, eco-solvent, latex and UV inkjet printing. Satin surface finish.

Water and weather-resistant paper. High scratch and folding resistance. For application to outdoor advertising panels or posters.

#### **FILM FEATURES:**

• Thickness (Indicative value)
150 µm

• Total weight (Indicative value)

130 g/m²

• Opacity (Indicative value) 98 %

#### **PRINTING GUIDE:**

- Use the HEXIS ICC profiles, available on our website www.hexis-graphics.com, to perform high quality work while optimising the ink quantity required for this substrate.
- · Comply with the conditions of storage temperature and hygometry before printing.
- · Touch-dry after less than 10 minutes depending on printer used.
- · Optimal drying time for the inks before laminating, coating or further processing is 24 hours.

#### **USER'S INSTRUCTIONS:**

- · Application of poster or wallpaper glue to the substrate and/or immersion of the paper.
- · The media can be rolled up or folded after gluing.

## **OPERATING RECOMMENDATIONS:**

The surface finish of your printings may be modified/improved/protected by applying the appropriate laminate: V650 or V700 (matt, satin or glossy).

It is recommended to laminate the PAP132DB film for any long-term outdoor exposure or if it is subject to severe climate conditions.

• In the event of frequent cleaning of the graphics, its edges and corners must be protected with a sealing tape or varnish.

#### STORAGE:



Storage period before use



Storage temperature

+10 °C to +30 °C (+50 °F to +86 °F)



Relative humidity during storage

with relative humidity between 30 % and 65 %



Storage method before use

in its unopened original packaging

#### NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.