



PETSAFE

PRODUCT DESCRIPTION:

Film composed of a 50-µm, ultra-transparent extruded PET. Intended to create a physical barrier between people preventing direct spread by droplet transmission.

FILM FEATURES:

- Thickness (Indicative value)
50 µm ±10 %
- Weight (Indicative value)
70 g/m² ±10 %
- Transparency (400-700 nm visible) (%) : (Indicative value)
> 90
- BRILLANCE (Indicative value)
> 99

USER'S INSTRUCTIONS:

- To be fastened on a frame using adhesive (e.g. cyanoacrylate, chloroprene, etc.), double-sided adhesive tape and/or staples, etc.
- Can be cleaned with hydroalcoholic solutions (such as SHA) or other usual detergents.
- Using abrasive sponges may scratch the film.

STORAGE:

- Storage period before use
2 years
- Storage temperature
+15 °C to +25 °C (+59 °F to +77 °F)
- Relative humidity during storage
with relative humidity of 50 %
- Storage area
in a dust-free environment
- Storage method before use
in its original packaging
- Orientation of rolls before use
vertically

DURABILITY:

- For short-term use.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. The measuring methods for the standards quoted above served as the basis for the development of our own measuring methods, which are available on request. Please feel free to contact us to get the latest instructions in use. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.