



## PM150V2



### PRODUCT DESCRIPTION:

150-µm, matt paper for solvent, eco-solvent, UV and latex inkjet printing. Ideal for printing indoor posters.

### FILM FEATURES:

- Thickness (Indicative value)  
**150 µm**
- Weight (Indicative value)  
**150 g/m<sup>2</sup>**
- Opacity (Indicative value)  
**> 96 %**

### PRINTING GUIDE:

- Touch-dry after less than 5 minutes depending on printer used.
- Optimal drying time for the inks before laminating, coating or further processing is 24 hours.

### USER'S INSTRUCTIONS:

- Operating temperature range: +10 °C to +30 °C (+50 °F to +86 °F)
- Relative humidity during application: with relative humidity between 30 and 65 %
- Laminating is possible with an adhesive-coated, transparent, cold-laminating film (HEXIS V700) or a thermal-bonding film (heat encapsulating) film.
- The surface finish of your printings may be modified/improved/protected by applying the appropriate V700 laminate (matt, satin or glossy).

### STORAGE:



Storage temperature  
**+10 °C to +30 °C (+50 °F to +86 °F)**



Relative humidity during storage  
**with relative humidity between 30 % and 65 %**



Storage area  
**in a dust-free environment**



Storage method before use  
**in its original packaging**



Orientation of rolls before use  
**vertically**

### NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).