



# POPSTART



## PRODUCT DESCRIPTION:

This 190-µm, opaque PP film is coated with a printable layer. Usable for solvent, eco-solvent, latex and UV inkjet printing. Aspect of the printable side: satin white.

## FILM FEATURES:

• Total thickness	(Average values) <b>190 µm</b>	Method <b>ISO 4593</b>
• Total weight	(Average values) <b>140 g/m<sup>2</sup></b>	Method <b>ISO 536</b>

## PRINTING GUIDE:

- Printable only on one side (outer side).
- Touch-dry after less than 10 minutes depending on the printer used.

## USER'S INSTRUCTIONS:

- Any handling of the product must be done with cotton clothes to avoid leaving fingerprints.
- Suitable for self-supporting and roll-up displays.

## STORAGE:



Storage period before use  
**1 year**



Storage temperature  
**+10 °C to +30 °C (+50 °F to +86 °F)**



Relative humidity during storage  
**with relative humidity between 35 % and 65 %**



Storage method before use  
**in its unopened original packaging**

## NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the absolute suitability of the medium for each specific application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not, however, constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).