



# SILICONE-COATED PAPER (N2PAPSILI)



## PRODUCT DESCRIPTION:

Silicone-coated Kraft paper 137 g/m<sup>2</sup>, stable under hygrometric variations. Protective liner.

## FILM FEATURES:

Thickness	(Indicative value) <b>140 μm</b>	
Total weight	(Average values) <b>137 g/m<sup>2</sup></b>	Method <b>HEXGSM001</b>
Relative humidity of paper	(Indicative value) <b>4.5 %</b>	

## LINER:

Stable under hygrometric variations

## ADHESIVE PROPERTIES:

Release	(Average values) <b>0.45 N/25 mm</b>	Method <b>HEXFTM010</b>
---------	---	----------------------------

## USER'S INSTRUCTIONS:

Operating temperature range: +10 °C to +30 °C (+50 °F to +86 °F)

Relative humidity during application: with relative humidity between 30 and 70 %

## STORAGE:



Storage period before use  
**1 year**



Storage temperature  
**+15 °C to +25 °C (+59 °F to +77 °F)**



Relative humidity during storage  
**with relative humidity of 50 %**



Storage method before use  
**in its unopened original packaging**

## NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. The measuring methods for the standards quoted above served as the basis for the development of our own measuring methods, which are available on request. Please feel free to contact us to get the latest instructions in use. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).