



VF180WM



PRODUCT DESCRIPTION:

260-µm film that is composed of a non-magnetic, ferrous layer and a polypropylene layer, which is printable by solvent, eco-solvent, latex and UV inkjet technology. Used in combination with the magnetic film FM580, the VF180WM film is intended for the removable marking on non-magnetic substrates. Matt white surface finish. For indoor use.

FILM FEATURES:

- Thickness (Indicative value)
260 µm
- Density (Indicative value)
4,4 g/cm³

PRINTING GUIDE:

- Touch-dry after less than 15 minutes depending on printer used.

USER'S INSTRUCTIONS:

- Dry application method
- Between -40 °C and +70 °C (-40 °F and +158 °F).
- Operating temperature range: -5 °C to +40 °C (+23 °F to +104 °F) with relative humidity between 10 % and 80 %.
- Storage temperature of the displayed graphic: 20 °C with a relative humidity of 30 %.
- The target surface and the back of the VF180WM film must be clean, dry and free from grease and metallic particles.

STORAGE:



Storage period before use
2 years



Storage temperature
+20 °C (+68 °F)



Relative humidity during storage
with relative humidity between 10 % and 80 %



Storage area
in a dust-free environment and protected from direct sun exposure



Storage method before use
in its unopened original packaging



Orientation of rolls before use
vertically

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.