



WALLPAPER2

PRODUCT DESCRIPTION:

Wall covering composed of a pre-pasted, non-woven, PVC-free paper. For solvent, eco-solvent, latex and UV inkjet printing. Interior application. Highly scratch-resistant. It has a satin surface finish.



FILM FEATURES:

• Total thickness	350 µm	
	(Average values)	Method
• Total weight	230 g/m²	ISO 536
	(Average values)	Method
• Opacity	85 %	ISO 2471

ADHESIVE:

- Water-based paste.
- Permanent adhesion after drying.

PRINTING GUIDE:

- Printable only on one side (outer side).
- Printing temperature ranging from 10 °C to 30 °C (+50 °F to +86 °F) with relative humidity between 30 % and 65 %.
- Touch-dry after less than 10 minutes depending on printer used.
- For any application, optimal drying time for the inks is 24 hours minimum.

USER'S INSTRUCTIONS:

- It is highly recommended to wear cotton gloves during any handling of the printed product.
- Cut the rolls into panels after printing.
- Indoor application to non-porous, smooth, dry and clean surfaces, which are free from any wallpaper and flaking paint residues.
- Paste humidification is done by immersing the entire WALLPAPER2 panel into the water tray for a maximum duration of 15 to 30 seconds. Once in the water, ensure that there is sufficient space between the wound film layers. Evacuate the water by pulling the panel out from one side to remove it from the water.

The soaking water must be changed after 6 to 7 immersed panels.

- Apply the film within the 2 minutes following its removal from the water.
- WALLPAPER2 applies like wallpaper.
- After application, immediately clean any excess paste with a damp sponge.

STORAGE:



Storage period before use
1 year



Storage temperature
+10 °C to +30 °C (+50 °F to +86 °F)



Relative humidity during storage
with relative humidity between 30 % and 65 %



Storage method before use
in its unopened original packaging

CERTIFICATION:

Fire-smoke classification



Fire-smoke classification standard
EN 13501-1:2018

Fire-smoke classification protocol no.
EFR-23-003977

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.