



PRODUCT DATA SHEET EASYPOSE

Product destined to facilitate wet application by reducing initial tack.

COMPOSITION:

- Water.
- Isopropanol.
- Surface-active agent / Detergent.

CHARACTERISTICS:

- Blue liquid.

USER'S GUIDE:

- Use at room temperature.
- The use of a vaporiser is recommended.
- Spray the surface for which the film is intended as well as the adhesive face of the film.
- Position the film.
- After application use a squeegee to wipe the solution and any air bubbles from the centre towards the edges.
- Use of a clean cloth recommended.
- Use in ventilated environment.
- Refer to the health and safety data sheet.
- Use goggles.

STORAGE:

- Keep container closed in a cool and ventilated environment.
- Shelf life: 1 year if kept unopened in the original container.

Note:

Because of the great variety of substrates and possible application methods the installer must examine the suitability of the media for each application. The methods of measuring for the standards quoted above are the basis for the development of our own measuring methods which are available on request (partial application). You are invited to enquire for the latest instructions in force.

All published data are based on measurements carried out regularly under laboratory conditions. They do, however, not constitute a warranty, representation or promise, express or implied as to the condition, quality, merchantability, fitness for a product, or that such product will satisfy any requirement for a specific property or capacity or special methods, all such warranties being hereby expressly disclaimed. The seller assumes no liability for claims beyond the replacement value of any product proven to be defective in material or workmanship and is in no way liable for direct, indirect, special, incidental damages or consequential loss including without limitation lost profits or loss of use, whether based on contract, tort or any other legal theory. Product specifications may change without prior notice. Our website is automatically updated: www.hexis-graphics.com.