



PRODUCT DATA SHEET

VR 7077

Edge sealing varnish for use around the edges of graphics in order to prolong their life.

COMPOSITION:

- Xylene
- Acrylic polymer

LIQUID FEATURES:

- Colourless to light yellow liquid.

USER'S INSTRUCTIONS:

- For professional use only.
- Refer to the safety data sheet prior to use.

The safety data sheet is available upon request.

- Apply the graphic to the desired substrate.
- In order to apply properly the varnish, affix masking tape to the substrate at 5 mm from the edge of the graphic. Do the same on the graphic at 5 mm from the edge. Please ensure that the edges of the graphic adhere well.
- Apply only to dry surfaces (graphic and substrate).
- Apply the varnish with a brush in one single layer.
- Remove the masking tape after a maximum of 15 minutes after application.
- The drying time depends upon the thickness of the varnish applied and upon the ambient temperature. For a film with an average coat, optimal drying time is 24 hours. Any physical aggression (cleaning, abrasion, etc.) must be avoided by all means during this period of time.
- Do not smoke while using.
- Use it in a properly ventilated area.
- Wear protective gloves and goggles.
- Once applied, the VR 7077 can be removed with acetone.

STORAGE:

- Keep the container tightly closed, in a cool and properly ventilated area. Keep it away from flames or sparks. Do not smoke.
- Shelf life: 1 year when stored in its unopened original container.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.