



## TECHNICAL DATA SHEET - PLOTTER VINYLs - PAPER TAPE

# HEX 100 HIGH TACK

110- $\mu$ m, stabilised paper, which is coated with a pressure-sensitive, rubber adhesive. Intended for creating and applying kits (logos, cut-out letters of ideally less than 5 cm (1.97 in.) etc.).

### **FILM FEATURES:**

	<u>Indicative values</u>
• Thickness ( $\mu$ m):	110
• Tensile strength (N/25 mm):	92
• Elongation at break (%):	14

### **ADHESIVE PROPERTIES:**

	<u>Indicative value</u>
• Adhesion to steel (N/25 mm):	2

### **ADHESIVE:**

- Natural rubber based.

### **USER'S INSTRUCTIONS:**

- Minimum recommended application temperature: +15 °C (+59 °F)
- Operating temperature range: +15 °C to +35 °C (+59 °F to +95 °F).
- This tape is suitable for applications requiring good stability over time (relative to dimensional stability and long-term storage) and moisture resistance.
- Good adhesion to the liner: reducing wrinkling, tunnelling and edge curling.

### **STORAGE:**

- Shelf life (before application):

The shelf life of this film is 1 year when stored unopened in its original packaging at a temperature of +21 °C (+70 °F) with relative humidity of 50 %.

### **NOTES:**

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).