



## TECHNICAL DATA SHEET - PLOTTER VINYLs - PAPER TAPE

# HEX 900 HIGH TACK 83 $\mu\text{m}$

83- $\mu\text{m}$  paper which is coated with a pressure-sensitive rubber adhesive.

### **FILM FEATURES:**

#### Indicative values

- |                                |    |
|--------------------------------|----|
| • Thickness ( $\mu\text{m}$ ): | 83 |
| • Tensile strength (N/25 mm):  | 88 |
| • Elongation at break (%):     | 3  |

### **ADHESIVE PROPERTIES:**

#### Indicative value

- |  |   |
|--|---|
| • Peel strength test on steel (N/25 mm): | 3 |
|--|---|

### **USER'S INSTRUCTIONS:**

- Recommended minimum application temperature: +15 °C (+59 °F).
- Operating temperature range: +15 °C to +35 °C (+59 °F to +95 °F).
- For best results, the letter transferring process should preferably be carried out on the same day that the transfer paper has been applied to the letters.

### **ADHESIVE:**

- Natural rubber based.
- Immediate adhesion.

### **STORAGE:**

- Shelf life (before application):

The shelf life of this film is 1 years when stored in its unopened original packaging at a temperature of 21 °C (70 °F) with relative humidity of 50 %.

### **NOTES:**

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).