



TECHNICAL DATA SHEET - PLOTTER VINYLs - PAPER TAPE

HEX 909 HIGH TACK

A 135- μm paper, which is coated with a pressure-sensitive rubber adhesive. Intended for the application of films that are difficult to transfer, such as etched glass films or films with structured surfaces.

FILM FEATURES:

	<u>Indicative values</u>
• Thickness (μm):	135
• Tensile strength (N/25 mm):	74
• Elongation at break (%):	4

ADHESIVE PROPERTIES:

	<u>Indicative value</u>
• Peel strength test on steel (N/25 mm):	6

ADHESIVE:

- Natural rubber based.

USER'S INSTRUCTIONS:

- Suitable for wet application.
- Good adhesion to the liner: reduction of folds, tunnelling and peeling off at the borders.
- Recommended minimum application temperature: +4 °C (+39 °F).
- Operating temperature range: from +4 °C to +55 °C (+39 °F to +131 °F).

STORAGE:

- Shelf life (before use):

The shelf life of this film is 1 year when stored unopened in its original packaging at a temperature of +22 °C (+72 °F) with relative humidity between 50 % and 55%.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.