



TECHNICAL DATA SHEET – SIGN VINYL – POLYPROPYLENE TAPE

HEX 910 MEDIUM TACK

98- μ m polypropylene film, which is coated with a pressure-sensitive, caoutchouc adhesive. Intended for the creation and application of kits.

FILM FEATURES:

	<u>Indicative values</u>
• Thickness (μ m):	98
• Tensile strength (N/25 mm):	66
• Elongation at break (%):	> 100

ADHESIVE FEATURES:

	<u>Indicative values</u>
• Adhesion to steel (N/25 mm):	3

ADHESIVE:

- Based on natural caoutchouc
- Immediate adhesion

USER'S INSTRUCTIONS:

- Minimum application temperature recommended: +15 °C (+59 °F)
- Operating temperature range: from +15 °C to +35 °C (from +59 °F to +95 °F)
- Resistant to humidity for long-term storage conditions
- Featuring a good dimensional stability, the HEX910 is stretch and kink resistant during application.

STORAGE:

- Shelf life (before application):

The shelf life of this film is 1 year if it is stored in its unopened original packaging at a temperature of 21 °C (70 °F), with relative humidity of 50 %.

NOTES:

Because of the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. All information released originates from laboratory measurements on a regular basis. However, it does not constitute a binding warranty. The seller is not held accountable for indirectly related damages beyond the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Updates of our specifications are automatically available on our website at www.hexis-graphics.com.