



TECHNICAL DATA SHEET - SIGN VINYL - EMBOSSED POLYPROPYLENE TAPE HEX 915

A 110- μm , embossed PP film, which is coated with a pressure-sensitive, acrylic adhesive.

FILM FEATURES:

Indicative value

- Thickness (μm): 110

ADHESIVE PROPERTIES:

(Measured average values at publication of the technical data sheet)

Indicative value

- Adhesion (N/cm): 1.1

ADHESIVE:

- Acrylic.
- Immediate adhesion.

USER'S INSTRUCTIONS:

- Dry application recommended.
- Minimum recommended application temperature: +10 °C (+50 °F).
- Operating temperature range: +15 °C to +35 °C (+59 °F to +95 °F).
- May be used for transferring glossy and matt films.
- Ideal for transferring letterings of between 5 cm and 31 cm (1.97 in. and 12.20 in.).
- For best results, the letter transferring process should preferably be carried out on the same day that the transfer film has been applied to the letters.

STORAGE:

- Shelf life (before application):

The shelf life of this film is 6 months when stored unopened in its original packaging at a temperature ranging from +15 °C to +25 °C (+59 °F to +77 °F) with relative humidity between 30 % and 70 %.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. The measuring methods for the standards quoted above served as the basis for the development of our own measuring methods which are available on request. Please feel free to contact us to get the latest instructions in use.

All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.