



DATA SHEET POLYPROPYLENE TAPE HEX 930 MEDIUM TACK

86 micron clear polypropylene film, coated with a pressure sensitive rubber adhesive. Intended for decal kits (cut letters and logos ideally between 5 cm and 31 cm / 2 in to 12 in...).

FILM CHARACTERISTICS:

	<u>Average values</u>
• Thickness (µm):	86
• Tensile strength (N/25mm):	48
• Elongation at break (%):	>100

ADHESIVE PROPERTIES:

(Average values measured when data sheet issued)

	<u>Average values</u>
• Adhesion on steel (N/25mm):	2.7

ADHESIVE:

- Rubber-based

USAGE GUIDE:

- Destined for dry application
- Minimum application temperature: +15 °C (+59 °F)
- Exposure temperature range: +15 °C to +35 °C (+59 °F to +95 °F)
- Tape for use with precision applications, layering, coloured films, be they calendered or cast
- Stable on the liner, excellent transparency and less tunnelling

STORAGE:

- Shelf life (before application):
6 month if stored unopened in the original packing at temperature between 15 °C and 25 °C (59 °F and 77 °F) and between 30 % and 70 % relative humidity.

NOTE:

Because of the great variety of substrates and new possible application methods, the user must examine the suitability of the media for each application. The methods of measurement in the quoted standards are used as a base to produce our own measurement methods, available on request. We prompt you to contact us to obtain the latest instructions in force.

All published data are based on measurements carried out regularly under laboratory conditions. They do not, however, constitute an intangible guarantee. The seller assumes no liability for indirect damage and will only assume financial responsible for a sum corresponding to the price of his products. All our specifications are subject to changes without prior notification. The specifications listed on our website are automatically updated: www.hexis-graphics.com.