



DATA SHEET EMBOSSED POLYERHTYLENE TAPE HEX 955

Transfer tape made up of an embossed polyethylene film with a thickness of 130µm, coated with a pressure sensitive acrylic adhesive.

CHARACTERISTICS OF THE FILM:

Average values

- | | |
|-------------------|-----|
| • Thickness (µm): | 130 |
|-------------------|-----|

ADHESIVE PROPERTIES:

(Average values measured when data sheet issued)

- | | |
|-------------------------------|-----|
| • Adhesion on steel (N/25mm): | 0.9 |
|-------------------------------|-----|

RECOMMENDATIONS:

- Dry application recommended.
- Ideal for transfer of letterings from 5cm to 31cm (2in to 12in).
- For best results, preferably perform the transfer within a day from applying the transfer film and transferring the letters.

ADHESIVE:

- Acrylic.
- Immediate adhesion.

STORAGE:

- Shelf life (before application):
6 months if stored in its original, unopened packing at a temperature between 15°C and 25°C (59°F to 77°F) and between 30 % and 70 % relative humidity.

NOTE:

Because of the great variety of substrates and new possible application methods, the user must examine the suitability of the media for each application. The methods of measurement in the quoted standards are used as a base to produce our own measurement methods, available on request. We prompt you to contact us to obtain the latest instructions in force.

All published data are based on measurements carried out regularly under laboratory conditions. They do not, however, constitute an intangible guarantee. The seller assumes no liability for indirect damage and will only assume financial responsible for a sum corresponding to the price of his products. All our specifications are subject to changes without prior notification. The specifications listed on our website are automatically updated: www.hexisgroup.com.