



TECHNICAL DATA SHEET - DIGITAL PRINTING - BANNER EFRONTOPAC

Banner of 610 g/m², for 2-face printing, suitable for standard solvent, eco-solvent, latex and UV inkjet printing. Matt surface finish.

BANNER FEATURES:

	<u>Average values</u>	<u>Standard</u>
• Total thickness (g/m ²):	610	
• Yarn/weft thread (Denier):	500 x 500	DIN EN ISO 2060
• Yarn/weft tear resistance (N):	235 / 220	DIN53356

GENERAL PRINTER COMPATIBILITIES:

	Solvent	Eco-solvent	Latex	UV
EFRONTOPAC	✓	✓	✓	✓

USER'S INSTRUCTIONS:

- For 2-face printing
- Touch-dry at the latest 10 minutes following application depending on the printer used.
- For any laminating and further processing, the optimum drying time of the inks is 24 hours minimum.
- Operating temperature range: from -20 °C to +60 °C (from -4 °F to 140 °F)
- To comply with the REACH regulation, we duly inform you about the presence of bis (2-ethylhexylphtalate) (DEHP).

STORAGE:

- Shelf life (before application):

The shelf life of this film is 1 year if it is stored at a temperature ranging from 15 °C to 25 °C (from 59 °F to 77 °F), with relative humidity of 50 %, in its original packaging, in an upright position, in a dust-free environment.

NOTES:

Because of the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. All information released originates from laboratory measurements on a regular basis. However, it does not constitute a binding warranty. The seller is not held accountable for indirectly related damages beyond the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Updates of our specifications are automatically available on our website at www.hexis-graphics.com.