



TECHNICAL DATA SHEET - DIGITAL PRINTING - MURAL TEXTILE - PERMANENT ADHESIVE

TEXWALL

270- μ m, adhesive-coated, white mural textile, which is composed of an acrylic-coated woven polyester fabric. Designed for solvent, eco-solvent, latex and UV printing.

FILM FEATURES:

	<u>Indicative value</u>	
• Thickness (μ m):	270	
	<u>Average values</u>	<u>Standard</u>
• Total weight of the product (g/m^2):	200	EN ISO 2286-2

GENERAL PRINTER COMPATIBILITES:

	Solvent	Eco-solvent	Latex	UV
TEXWALL	✓	✓	✓	✓

LINER:

- 50- μ m silicone-coated paper.

ADHESIVE:

- Immediate and permanent adhesion.

USER'S INSTRUCTIONS:

- Touch-dry after less than 10 minutes depending on the printer used.
- Edge-to-edge indoor application.
- Adhesion to regular smooth and dry surfaces, such as glass, steel, aluminium, PVC, concrete, acrylic, etc. except cardboards (painted or not), plaster walls, wallpaper, substrates once stripped off the wallpaper ...
- Operating temperature range: 10 °C to 70 °C (50 °F to +158 °F).
- Cleaning must be carried out with slightly soapy water (neutral pH soap) using non-abrasive accessories.

Before cleaning, always carry out a test on a small, inconspicuous area of the product.

STORAGE:

- Shelf life (before use):

The shelf life of this film is 1 year when stored upright and unopened in its original packaging in a dust-free environment at a temperature ranging from 10 °C to 35 °C (50 °F to 95 °F) with relative humidity of 50 %.

DURABILITY:

- Vertical indoor exposure, unprinted: 2 years.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application.

All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.