



TECHNICAL DATA SHEET - DIGITAL PRINTING - PAINTING CANVAS

CANVAS 3

A 450- μ m white painting CANVAS, composed of cotton and polyester. Designed for solvent, eco-solvent, latex and UV printing.

FILM FEATURES:

Average values

- Thickness (μ m): 450
- Total weight of the product (g/m^2): 300
- Yarn/weft thread (TEX) 29.5 x 50

GENERAL PRINTER COMPATIBILITIES:

	Solvent	Eco-solvent	Latex	UV
CANVAS3	✓	✓	✓	✓

USER'S INSTRUCTIONS:

- Touch dry after less than 5 minutes depending on printer used.
- Good resistance to abrasion.
- Substrate/Printing sensitive to water splashing as well as fingerprints (gloves strongly recommended).
- Operating temperature range: +15 °C to +25 °C (+59 °F to +77 °F) with 30-70 % humidity.

STORAGE:

- Shelf life (before use):

The shelf life of this film is 1 year when stored upright and unopened in its original packaging in a dust-free environment at a temperature ranging from +15 °C and +25 °C (+59 °F to +77 °F) with relative humidity of 50 %.

DURABILITY:

- The durability of the printing depends on the printing technology used and the inks used.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.