



## TECHNICAL DATA SHEET - DIGITAL PRINTING - BANNER FRONT4v4

A 370- $\mu\text{m}$ , hot-laminated banner, composed of polyester and PVC. Designed for standard solvent, eco-solvent, latex and UV inkjet printing. FRONT4v4 is intended for use as an advertising/event banner. Printable on the inner side. Satin surface finish.

### **BANNER FEATURES:**

	<u>Indicative values</u>	
• Total thickness of the product ( $\mu\text{m}$ ):	370	
• Total weight of the product ( $\text{g}/\text{m}^2$ ):	440	
• Yarn/weft thread (DTEX):	1000 x 1000	
	<u>Average values</u>	<u>Standard</u>
• Yarn/weft tear resistance (N):	90 / 85	ISO 13937-2: 2000

### **GENERAL PRINTER COMPATIBILITIES:**

	Solvent	Eco-solvent	Latex	UV
<b>FRONT4v4</b>	✓	✓	✓	✓

### **USER'S INSTRUCTIONS:**

- FRONT4v4 is specially intended for use as an tautly stretched advertising/event banner. Recurrent folding or creasing may provoke premature damage to the banner.
- Printing temperature range: +18 °C to +25 °C (64 °F to 77 °F).
- Printable on the inner side.
- Touch-dry after less than 5 minutes depending on printer used.
- Optimal drying time for the inks is 24 hours minimum.

### **STORAGE:**

- Shelf life (before application):

The shelf life of this film is 1 year when stored unopened in its original packaging at a temperature ranging from 18 °C to 25 °C (+64 °F to +77 °F) with relative humidity between 40 % and 60 %.

### **DURABILITY:** (Central European climate)

- Vertical outdoor exposure, unprinted: 1 year.

### **NOTES:**

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).