



## TECHNICAL DATA SHEET – DIGITAL PRINTING – PAPER

### P130

148-µm paper, suitable for standard solvent, eco-solvent, latex and UV inkjet printing. Satin surface finish.

#### **PAPER FEATURES:**

	<u>Average values</u>
• Total thickness (µm):	148
• Total weight (g/m <sup>2</sup> ):	130
• Opacity (%):	> 89

#### **GENERAL PRINTER COMPATIBILITY:**

	<b>Solvent</b>	<b>Eco-solvent</b>	<b>Latex</b>	<b>UV</b>
<b>P130</b>	✓	✓	✓	✓

#### **USER'S INSTRUCTIONS:**

- Use the HEXIS ICC profiles available on our website at [www.hexis-graphics.com](http://www.hexis-graphics.com) to achieve high quality results while optimising the ink quantity necessary for the substrate.
- Touch-dry at the latest 5 minutes following application depending on the printer used.
- Respect the storage conditions relative to temperature and hygrometry before printing.
- Weather-resistant and water-repellent paper surface

#### **RECOMMENDATIONS:**

- For any laminating, coating and further processing, the optimum drying time of inks is 24 hours.
- The print appearance can be modified/improved/protected by applying the V650 or V700 laminate (matt, satin or gloss).

*It is recommended to laminate the P130 for any long-term outdoor exposure or if it is subject to severe climate conditions.*

- The latex inks are water-sensitive and need to be protected in case of outdoor exposure.
- In the event of frequent cleaning of the graphic, the edges and corners must be protected with a sealing tape or varnish.

#### **STORAGE:**

- Shelf life (before application):

The shelf life of this film is 1 year if it is stored in its unopened original packaging, at a temperature ranging from 10 °C to 30 °C (from 50 °F to 86 °F), with relative humidity between 30 % and 65 %.

#### **NOTES:**

Because of the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. The measuring methods for the standards quoted above served as basis for the development of our own measuring methods which are available on request. Please feel free to contact us to get the latest instructions in use. All information released originates from laboratory measurements on a regular basis. However, it does not constitute a binding warranty. The seller is not held accountable for indirectly related damages beyond the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Updates of our specifications are automatically available on our website at [www.hexis-graphics.com](http://www.hexis-graphics.com).