



## DATA SHEET - DIGITAL PRINTING - SATIN PAPER

### PAP132DB

Coated multilayer paper, 130 g/m<sup>2</sup>, with blue back. For solvent, eco-solvent, latex and UV inkjet printing. Satin surface finish.

Water and weather-resistant paper. High scratch and folding resistance. For application to outdoor advertising panels or posters.

#### **FILM FEATURES:**

##### Indicative values

- Thickness (µm): 150
- Weight (g/m<sup>2</sup>): 130
- Opacity (%): 98

#### **GENERAL PRINTER COMPATIBILITIES:**

	<b>Solvent</b>	<b>Eco-solvent</b>	<b>Latex</b>	<b>UV</b>
<b>PAP132DB</b>	✓	✓	✓	✓

#### **USER'S INSTRUCTIONS:**

- Use the ICC HEXIS profiles available on our website at [www.hexis-graphics.com](http://www.hexis-graphics.com) to perform high quality work while optimising the quantity of ink required for this substrate.
- Respect the preheating and drying temperatures for the films recommended by the ink and printer manufacturers.
- Touch-dry after less than 10 minutes depending on the printer used.
- Application of poster or wallpaper glue to the substrate and/or immersion of the paper.
- The media can be rolled-up or folded after gluing.

#### **OPERATING RECOMMENDATIONS:**

- For any lamination, coating or other, optimal drying time for the inks is 24 hours.
- The surface finish of your printing may be modified/improved/protected by a judicious choice of laminating films V650/V700 Matt, Satin or Glossy.

*It is recommended to laminate the PAP132DB for any long-term outdoor exposure or if it is subject to severe climate conditions.*

- In the event of frequent cleaning of the graphics, its edges and corners must be protected with a sealing tape or varnish.

**STORAGE:**

- Shelf life (before application):

The shelf life of this film is 1 year when stored unopened in its original packaging at a temperature ranging from +10 °C to +30 °C (+50 °F to +86 °F) with relative humidity between 30 % and 65 %.

**NOTES:**

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application.

The measuring methods for the standards quoted above served as basis for the development of our own measuring methods which are available on request. Please feel free to contact us to get the latest instructions in use.

All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).