



DATA SHEET - DIGITAL PRINTING - MATT PAPER

PM 150 V2

175- μ m, matt paper for solvent, eco-solvent, UV and latex inkjet printing. Ideal for printing indoor posters.

PAPER FEATURES:

Indicative values

- | | |
|-------------------------|------|
| • Thickness (μ m): | 175 |
| • Weight (g/m^2): | 150 |
| • Opacity (%): | > 98 |

GENERAL PRINTER COMPATIBILITIES:

	Solvent	Eco-solvent	Latex	UV
PM 150 V2	✓	✓	✓	✓

USER'S INSTRUCTIONS:

- Operating temperature range: from +10 °C to +30 °C (+50 °F to +86 °F) with 30-65 % humidity.
- Touch-dry after less than 5 minutes depending on printer used.
- Laminating is possible with an adhesive-coated, transparent, cold-laminating film (HEXIS V700) or a thermal-bonding film (heat encapsulating) film.
- The surface finish of your printing may be modified/improved/protected by applying the laminating film V700 featuring a matt, satin or glossy surface finish.
- For any lamination, coating or other, optimal drying time for the inks is 24 hours.

STORAGE:

- Storage conditions (before use):

To be stored upright in its original packaging, in a dust-free environment, at a temperature ranging from +10 °C to +30 °C (+50 °F to +86 °F) with relative humidity between 30 % and 65 %.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. The measuring methods for the standards quoted above served as the basis for the development of our own measuring methods which are available on request. Please feel free to contact us to get the latest instructions in use.

All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.