



TECHNICAL DATA SHEET - DIGITAL PRINTING - LIGHT-DIFFUSING OPAQUE POLYESTER
POD 130 SOLV

130- μ m, light-diffusing, opaque polyester film, which is intended for solvent and eco-solvent inkjet printing. For application in light boxes, application panels etc.

FILM FEATURES:
Average values

- Thickness (μ m): 130
- Weight (g/m^2): 180

GENERAL PRINTER COMPATIBILITIES:

	Solvent	Eco-solvent
POD 130 SOLV	✓	✓

USER'S INSTRUCTIONS:

- The printable side is the matt one.
- Backlit with printed side visible.
- Substrate/Printing sensitive to water splashing as well as fingerprints (gloves strongly recommended).
- Touch-dry after less than 5 minutes depending on printer used.
- Any not-sticked film must be held between two clear rigid supports.
- Operating temperature range: +10 °C to +30 °C (+50 °F to +86 °F) with 35-65 % humidity.
- The printed films must be solely stored in flat position, never rolled up.

OPERATING RECOMMENDATIONS:

- For outdoor applications, it is recommended to apply a laminate to the film while keeping some overhang material. For this purpose, use an adhesive-coated cold laminating film V700 with matt, satin or glossy surface finish to modify / improve / protect your prints.
- For any lamination, coating or other, optimal drying time for the inks is 24 hours.

STORAGE:

- Shelf life (before use):

The shelf life of this film is 1 year when stored upright in its original packaging in a dust-free environment at a temperature ranging from +10 °C to +30 °C (+50 °F to +86 °F) with relative humidity between 35 % and 65 %.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application.

The measuring methods for the standards quoted above served as the basis for the development of our own measuring methods which are available on request. Please feel free to contact us to get the latest instructions in use.

All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.