



## TECHNICAL DATA SHEET - DIGITAL PRINTING – POLYPROPYLENE - OPAQUE POP200ECOS

205- $\mu$ m, white/grey, opaque polypropylene film. For solvent, eco-solvent, latex and UV inkjet printing. Satin surface finish.

### FILM FEATURES:

#### Indicative values

- Total thickness of the product ( $\mu$ m): 205
- Total weight of the product ( $g/m^2$ ): 170

### GENERAL PRINTER COMPATIBILITIES:

	Solvent	Eco-solvent	Latex	UV
<b>POP200ECOS</b>	✓	✓	✓	✓

### USER'S INSTRUCTIONS:

- Printing temperature range: +15 °C to +30 °C (+59 °F to +86 °F) with 30-60 % humidity.

*For latex printing, always carry out a preliminary test to define optimal adjustment of printing parameters and ink drying temperatures in order to avoid any risk of material deformation.*

- Touch-dry after less than 10 minutes depending on printer used.
- Suitable for roll-up and wall displays.

*Anti-curling film: prevents self-curling. Scratch-resistant film: protective lamination not necessary.*

- The surface finish of your printing may be modified/improved by the judicious choice of one of the laminating films V650, V700, V750 or GFLI130. **DO NOT USE** heat-sealing (heat encapsulating) film.

*During lamination, make sure that the tension between the protection film and the visual is the same in order to avoid any unwanted curling effect.*

- For any lamination, coating or other, optimal drying time for the inks is 24 hours.

### STORAGE:

- Shelf life (before application):

The shelf life of this film is 1 year when stored unopened in its original packaging at a temperature ranging from +10 °C to +30 °C (+50 °F to +86 °F) with relative humidity between 35 % and 65 %.

### NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).