



TECHNICAL DATA SHEET - DIGITAL PRINTING - POLYESTER - OPAQUE POP 310 ECOS

Film composed of a 310- μ m white/silver opaque colaminated polyester, intended for solvent, eco-solvent and latex inkjet printing. Specially adapted for use on POP Displays.

FILM FEATURES:

	<u>Average values</u>	<u>Standard</u>
• Total thickness of the product (μ m):	310	
• Total weight of the product (g/m^2):	420	HEXGSM001
• Opacity (%):	> 99	HEXOPA001

GENERAL PRINTER COMPATIBILITIES:

	Solvent	Eco-solvent	Latex
POP310ECOS	✓	✓	✓

USER'S INSTRUCTIONS:

- Touch dry after less than 10 minutes depending on printer used.
- Operating temperature range: +10 °C to +30 °C (from +50 °F to +86 °F) with 30-70 % humidity.
- Substrate/Printing sensitive to water splashing and fingerprints (wearing gloves and wiping the surface of the product with a cotton cloth before printing are highly recommended).
- Substrate/Printing susceptible to tearing; handle the edges carefully.
- The grey rear side may be susceptible to scratching. Handle with care.

OPERATING RECOMMENDATIONS:

- For any lamination, coating or other, optimal drying time for the inks is 24 hours.
- The surface finish of your printing may be modified/improved/protected by a judicious choice of laminating films V700 (Matt, Satin or Glossy) or PSPOP.

STORAGE:

- Shelf life (before application):

The shelf life of this film is 1 year when stored upright in its original packaging in a dust-free environment at a temperature ranging from +15 °C and +25 °C (+59 °F to +77 °F) with relative humidity of 50 %.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. The measuring methods for the standards quoted above served as basis for the development of our own measuring methods which are available on request. Please feel free to contact us to get the latest instructions in use. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.