



TECHNICAL DATA SHEET - DIGITAL PRINTING - MULTILAYER FILM POPPRIMO

Multilayer film composed of a 220- μm white/white opaque PVC and boPET. For solvent, eco-solvent, latex and UV inkjet printing. Matt white surface finish.

FILM FEATURES:

Indicative values

- Total thickness of the product (μm): 220
- Total weight of the product (g/m^2): 290

GENERAL PRINTER COMPATIBILITIES:

	Solvent	Eco-solvent	Latex	UV
POPPRIMO	✓	✓	✓	✓

USER'S INSTRUCTIONS:

- Printing temperature range: +15 °C to +30 °C (+59 °F to +86 °F) with 30-60 % humidity.
- Printing on the grain face (outer side of the roll).
- Touch dry after less than 10 minutes depending on printer used.
- Suitable for roll-up and wall displays.

OPERATING RECOMMENDATIONS:

- For any lamination, coating or other, optimal drying time for the inks is 24 hours.
- The surface finish of your printing may be modified/improved by the judicious choice of one of the laminating films V650, V700, V750 or PSPOP. DO NOT USE heat-sealing (heat encapsulating) film.

STORAGE:

- Shelf life (before application):

The shelf life of this film is 2 years when stored upright and unopened in its original packaging at a temperature ranging from +12 °C to +32 °C (+54 °F to +90 °F) with relative humidity between 45 % and 65 %.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.