



CANVAS4



PRODUCT DESCRIPTION:

A 340-µm, white painting CANVAS, composed of polyester. Designed for solvent, eco-solvent, latex and UV printing. It has a satin surface finish.

FILM FEATURES:

- Thickness (Indicative value)
340 µm
- Total weight (Indicative value)
260 g/m²

PRINTING GUIDE:

- Printable only on one side (outer side).
- Printing temperature ranging from 10 °C to 35 °C (+50 °F to +95 °F) with relative humidity between 30 % and 75 %.
- Touch-dry after less than 10 minutes depending on printer used.
- Optimal ink drying time: 12 hours.

STORAGE:



Storage period before use
1 year



Storage area
in a dark place



Storage temperature
+10 °C to +30 °C (+50 °F to +86 °F)



Storage method before use
in its original packaging



Relative humidity during storage
with relative humidity between 30 % and 75 %

DURABILITY: (Central European climate)

- The durability of the print depends on the printing technology and the inks used.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.