

TECHNICAL DATA SHEET





GLITFLEX

PRODUCT DESCRIPTION:

Thermal bonding film with glitter effect, suitable for heat transfer applications to cotton, polyester and mixed fabrics. Perfectly suitable for the creation of medium- and large-sized logos and images.

FILM FEATURES:

· Film thickness

(Indicative value) 330 µm

LINER:

· 100-µm polyester backing paper.

APPLICATION GUIDE FOR FLEX:

Good adhesion to cotton, polyester and mixed fabrics. Carry out a test to check the resistance of the fabric to the press temperature and the compatibility of the flex film with the cloth.

Cutting and weeding

- · Cut the mirror image with the plotter through the protector.
- Using a blade in good shape, at a 45-degree angle:
- · Applying high pressure;
- · Cutting size: large-sized logos.
- Weed slowly after cutting.



Pressing temperature





Pressing duration

10 secondes

Carefully remove the transfer tape while the film is still:



Protector removal

hot



STORAGE:



Storage period before use

1 vear



Storage temperature

+15 °C to +25 °C (+59 °F to +77 °F)



Relative humidity during storage

with relative humidity between 30 % and 70 %



Storage method before use

in its unopened original packaging



Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.





with a maximum of 40 °C (104 °F)



Washing conditions

Turn your garment inside out for washing and use laundry products without chlorine bleach.

Iron the textile inside out or protect the flex film

with a pressing cloth, at low temperature,



Drying conditions

Tumble drying is prohibited.



Ironing conditions

without using steam.



