

TECHNICAL DATA SHEET





POPPRIMO









PRODUCT DESCRIPTION:

This 270-µm, white/grey, opaque PP film is coated with a printable layer. Usable for solvent, eco-solvent, latex and UV inkjet printing. Aspect of the printable side: matt white.

FILM FEATURES:

•	Total thickness	(Average values)	Method
		270 μm	ISO 4593

Total weight
(Average values)
205 g/m²
ISO 536

PRINTING GUIDE:

- · The outer side of the roll (white side) is printable.
- · Touch-dry after less than 10 minutes depending on the printer used.

USER'S INSTRUCTIONS:

· Suitable for self-supporting and roll-up displays.

STORAGE:



Storage period before use

1 year



Storage temperature

+15 °C to +25 °C (+59 °F to +77 °F)



Relative humidity during storage

with relative humidity between 40 % and 60 %



Storage method before use

in its unopened original packaging

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the absolute suitability of the medium for each specific application. All of the published information is based on measurements regularly performed in the laboratory. All the published information does not, however, constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.