



VM380WM



PRODUCT DESCRIPTION:

300-µm multilayer film, which is composed of a magnetic plastic film with a pole width of 1.5 mm and a white printable layer. It allows removable marking on ferrous substrates. For solvent, eco-solvent, latex and UV inkjet printing. Matt surface finish. For indoor use.

FILM FEATURES:

- Thickness (Indicative value)
300 µm
- Magnetic force (Indicative value)
5 g/cm²

PRINTING GUIDE:

- Before printing, certain printer parameters must be properly adjusted to make sure of the correct media feeding.
- *Attention : Upon the printer used, the film may adhere to the printer's input/output plate.*
- Touch-dry after less than 15 minutes depending on printer used.

USER'S INSTRUCTIONS:

- Maximum operation temperature: **+70 °C**
- For indoor purposes only.
- The target surface and the back of the magnetic film must be clean, dry and free from grease and metallic particles.

STORAGE:



Storage period before use
1 year



Storage temperature
+20 °C (+68 °F)



Relative humidity during storage
with relative humidity between 10 % and 80 %



Storage method before use
in its unopened original packaging

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.