



PRODUCT DATA SHEET HEXISOAP

HEXISOAP is a concentrated soap that facilitates the wet application of adhesive-coated films (BODYFENCE range, V202CG1, Cristal, sun protection films, PURE ZONE[®], etc.). HEXISOAP reduces the grip of the adhesive. It also saves time necessary for positioning the film on the surface to be covered, while ensuring good adhesion of the film to the substrate.

COMPOSITION:

- Water.
- Anionic surfactants: < 10 %.

LIQUID FEATURES:

• Colourless liquid.

USER'S INSTRUCTIONS:

• It is recommended to wear protective equipment (gloves, goggles).

The safety data sheet is available upon request.

- Dilute the HEXISOAP concentrate with water in a sprayer:
 - Dosage for a Bodyfence film: Press once on the dispenser bottle per litre of water (about 2 ml).
 - Dosage for wet application of other films: Press 2 to 4x on the dispenser bottle per litre of water (ranging from 4 to 8 ml).

Carry out a test application with the indicated diluted solution. The dosage of the HEXISOAP concentrate must be adapted to the respective temperature conditions (high or low temperature).

- Shake the sprayer well with the diluted solution before use.
- Thoroughly spray the diluted HEXISOAP on the application surface and each side of the film.
- Position and adjust the film on the substrate.
- The film must be evenly squeegeed to remove all HEXISOAP residues.

STORAGE:

- Keep the HEXISOAP in its original container, securely closed, at ambient temperature and protected from direct sunlight.
- Shelf life: I year when stored in its unopened original container.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.