



TECHNICAL DATA SHEET - TAPE

HEX 750

A 100- μm transparent film, which is coated with a pressure-sensitive acrylic adhesive.

FILM FEATURES:

	<u>Average values</u>
• Thickness of film (μm):	100
• Thickness of film + adhesive (μm):	120

LINER:

- Silicone-coated paper 60 g/m².

ADHESIVE PROPERTIES:

	<u>Average values</u>	<u>Standard</u>
• Peel strength test 180° on glass (N/25 mm): after 20 minutes of application	I	HEXFTM001

ADHESIVE:

- Acrylic.

USER'S INSTRUCTIONS:

- This tape is especially suitable for:
 - For transferring the carbon effect film S5CANB and the fluorescent films of the F610 series. Dry application.
 - For transferring the printable flex films FLEX UFI200 and UFI400.
- For more information on the application method of the tape HEX750 with textile films, please refer to the Application Guide FLEX DIGITAL PRINTING on the "Professionals" pages, category "Digital printing media" on the site www.hexis-graphics.com.

STORAGE:

- Shelf life (before use):

The shelf life of this film is 1 year when stored upright and unopened in its original packaging in a dust-free environment at a temperature ranging from +15 °C and +25 °C (+59 °F to +77 °F) with relative humidity of 50 %.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.