



TECHNICAL DATA SHEET – SIGN VINYL – PAPER TAPE

HEX 100 HIGH TACK

110- μ m, stabilised paper, which is coated with a pressure-sensitive, caoutchouc adhesive. Intended for the creation and application of kits (logos, cut letterings of ideally less than 5 cm, etc.).

FILM FEATURES:

	<u>Indicative values</u>
• Thickness (μ m):	110
• Tensile strength (N/25 mm):	92
• Elongation at break (%):	14

ADHESIVE FEATURES:

	<u>Indicative values</u>
• Adhesion to steel (N/25 mm):	4

ADHESIVE:

- Based on natural caoutchouc

USER'S INSTRUCTIONS:

- Minimum application temperature recommended: +15 °C (+59 °F)
- Operating temperature range: from +15 °C to +35 °C (from +59 °F to +95 °F)
- This tape is suitable for applications requiring good stability over time (relative to dimensional stability and long-term storage) and moisture resistance.
- Good adhesion to the liner: reducing wrinkling, tunnelling and edge curling

STORAGE:

- Shelf life (before application):

The shelf life of this film is 1 year if it is stored in its unopened original packaging at a temperature of 21 °C (70 °F), with relative humidity of 50 %.

NOTES:

Because of the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. All information released originates from laboratory measurements on a regular basis. However, it does not constitute a binding warranty. The seller is not held accountable for indirectly related damages beyond the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Updates of our specifications are automatically available on our website at www.hexis-graphics.com.