



TECHNICAL DATA SHEET – SIGN VINYL – PAPER TAPE HEX 90I LOW TACK

83- μ m paper which is coated with a pressure-sensitive, caoutchouc adhesive.

FILM FEATURES:

	<u>Indicative values</u>
• Thickness (μ m):	83
• Tensile strength (N/25 mm):	88
• Elongation at break (%):	3

ADHESIVE FEATURES:

	<u>Indicative values</u>
• Adhesion to steel (N/25 mm):	3

ADHESIVE:

- Based on natural caoutchouc
- Immediate adhesion

USER'S INSTRUCTIONS:

- Minimum application temperature recommended: +15 °C (+59 °F)
- Operating temperature range: from +15 °C to +35 °C (from +59 °F to +95 °F)
- For enhanced outcomes, the final application process must preferably be carried out on the same day than the transfer of the letters on the tape.

STORAGE:

- Shelf life (before application):

The shelf life of this film is 1 year if it is stored in its unopened original packaging at a temperature of 21 °C (70 °F), with relative humidity of 50 %.

NOTES:

Because of the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. All information released originates from laboratory measurements on a regular basis. However, it does not constitute a binding warranty. The seller is not held accountable for indirectly related damages beyond the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Updates of our specifications are automatically available on our website at www.hexis-graphics.com.