



TECHNICAL DATA SHEET - SIGN VINYL - EMBOSSED POLYPROPYLENE TAPE

HEX 905 HIGH TACK 110 μm

A 110- μm embossed PP film, which is coated with a pressure-sensitive acrylic adhesive.

FILM FEATURES:

Average values

- Thickness (μm): 110

ADHESIVE PROPERTIES:

Average values

- Adhesions (N/cm): 1.1
- Resistance to solvents: the adhesive is resistant to most chemicals (alcohol, petrol, diluted acids, oils, fuels).

ADHESIVE:

- Acrylic.
- Immediate adhesion, suitable for wet application.

USER'S INSTRUCTIONS:

- Recommended minimum application temperature: +10 °C (+50 °F).
- Operating temperature range: +15 °C to +35 °C (+59 °F to +95 °F).
- For best results, it is preferable to perform the transfer operation during the daytime between application of the transfer film and transfer of the letters.

STORAGE:

- Shelf life (before application):

The shelf life of this film is 6 months when stored unopened in its original packaging at a temperature ranging from +15 °C to +25 °C (+59 °F to +77 °F) with relative humidity between +30 % and 70 %.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.