



TECHNICAL DATA SHEET - PLOTTER VINYL STRONGBAN3

Pressure-sensitive, acrylic, self-adhesive tape, which is coated on a protection liner. Intended for doing hems on PVC banners.

ADHESIVE FEATURES:

- | | <u>Indicative value</u> |
|-------------------|-------------------------|
| • Thickness (µm): | 125 |

LINER:

- Multilayered, removable, white film with 3 mm overhang on both sides.

ADHESIVE PROPERTIES:

- | | <u>Indicative value</u> |
|---|-------------------------|
| • Adhesion to steel after 20 minutes (N/25 mm): | 41 |

USER'S INSTRUCTIONS:

- Recommended minimum application temperature: +18 °C (+64 °F).
- Operating temperature range: from -40 °C to +95 °C (-40 °F to +203 °F).
- Highly UV-resistant.
- The target surfaces must be clean, dry and free from dust, grease, oil and any other contaminating agent.
- For applications requiring strong adhesion, bonding of textured materials and decorative parts.
- The product must be protected from dust, heat, humidity, direct sunlight and solvent emanations.

STORAGE:

- Shelf life (before application):

The shelf life of this film is 1 year when stored upright in its unopened original packaging at a temperature not exceeding 24 °C (75 °F).

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.