



TECHNICAL DATA SHEET - DIGITAL PRINTING - BANNER EFRONTOPAC

A banner of 610 g/m² that is printable on both sides and that is suitable for standard solvent, eco-solvent, UV and latex inkjet printing. Matt surface finish.

BANNER FEATURES:

	<u>Average values</u>	<u>Standard</u>
• Total weight of the product (g/m ²):	610	
• Yarn/weft thread (Denier):	500 x 500	DIN EN ISO 2060
• Yarn/weft tear resistance (N):	235/220	DIN53356

GENERAL PRINTER COMPATIBILITIES:

	Solvent	Eco-solvent	Latex	UV
EFRONTOPAC	✓	✓	✓	✓

USER'S INSTRUCTIONS:

- Printable on both sides.
- Touch-dry after less than 10 minutes depending on printer used.
- Optimal drying time for the inks before laminating or further processing is 24 hours minimum.
- Operating temperature range: -20 °C to +60 °C (-4 °F to +140 °F).

STORAGE:

- Shelf life (before application):

The shelf life of this film is one year when stored upright in its original packaging in a dust-free environment at a temperature ranging from 15 °C to 25 °C (+59 °F to +77 °F) with relative humidity of 50 %.

CERTIFICATIONS:

- The EFRONTOPAC banner complies with REACH. It does not contain any substances referenced in ECHA's list of SVHC (Substances of very high concern).

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.