



TECHNICAL DATA SHEET - DIGITAL PRINTING - DIFFUSING TEXTILE

TEXAIR

220- μ m white textile, which is composed of a polyurethane-coated woven polyester fabric. Designed for latex and UV printing. Product classified B1 (test report PZ-Hoch-141005-2) according to DIN 4102 fire behaviour of building materials.

FILM FEATURES:

	<u>Indicative value</u>	
• Thickness (μ m):	220	
	<u>Average value</u>	<u>Standard</u>
• Total weight of the product (g/m^2):	200	EN ISO 2286-2

GENERAL PRINTER COMPATIBILITIES:

	Latex	UV
TEXAIR	✓	✓

USER'S INSTRUCTIONS:

- For storage, the product must be wound or kept in flat position in order to avoid pressure marks.
- Touch dry after less than 10 minutes depending on printer used.
- Indoor use only.
- Intended for fixing in a tension frame with a silicone strip, to be used for frontlit and backlit applications, exhibition stands, etc.

Product classified B1 according to DIN 4102 fire behaviour of building materials (test report PZ-Hoch-141005-2).

STORAGE:

- Shelf life (before use):

The shelf life of this film is 1 year when stored upright and unopened in its original packaging in a dust-free environment at a temperature ranging from 10 °C to 35 °C (+59 °F to +77 °F) with relative humidity of 50 %.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.