



## TECHNICAL DATA SHEET - DIGITAL PRINTING - PVC - REMOVABLE ADHESIVE EASYSYTIKWS

Film composed of a 150- $\mu\text{m}$ , monomeric, calendered PVC, which is coated with a pressure-sensitive, removable acrylic adhesive for short-term use. For solvent, eco-solvent, latex and UV inkjet printing. Satin surface finish. This product is B-s1, d0 classified according to the French standard for fire behaviour (protocol no. EFR-21-000058).

### FILM FEATURES:

	<u>Indicative values</u>	
• Thickness ( $\mu\text{m}$ ):	150	
• Total thickness of the product ( $\mu\text{m}$ ):	300	
	<u>Average values</u>	<u>Standard</u>
• Total weight of the product ( $\text{g}/\text{m}^2$ ):	360	HEXGSM001
• Tensile strength (N/25 mm):	min. 50	HEXNFX41021
• Elongation at break (%):	min. 100	HEXNFX41021
• Shrinkage 168 hours at 70 °C (158 °F) (mm):	< 1	HEXRET001

### GENERAL PRINTER COMPATIBILITES:

	Solvent	Eco-solvent	Latex	UV
<b>EASYSYTIKWS</b>	✓	✓	✓	✓

### LINER:

- Silicone-coated Kraft paper 137  $\text{g}/\text{m}^2$ , with light blue HEXIS print.
- Stable under hygrometric variations.

### ADHESIVE PROPERTIES:

(Measured average values at publication of the technical data sheet)

	<u>Average values</u>	<u>Standard</u>
• Peel strength test 180° on glass (N/25 mm):		HEXFTM001
after 20 minutes of application	2	
after 24 hours of application	3	
• Initial tack (N/25 mm):	7	HEXFTM009
• Release (N/25 mm):	0.1	HEXFTM003
• Resistance to solvents: the adhesive is resistant to most chemicals (alcohol, diluted acids, oils).		

### ADHESIVE:

- Solvent-based acrylic adhesive.
- Immediate adhesion; removable adhesive.

**USER'S INSTRUCTIONS:**

- This product is B-s1, d0 classified according to the French standard for fire behaviour (protocol no. EFR-21-000058).
- Touch-dry after less than 10 minutes depending on printer used.
- After printing, a minimum ink drying time of 24 hours must be applied before:
  - plotting in areas with heavy ink loads;
  - coating the graphic;
  - any further processing.
- Do not leave the media on the printer while stopped.

*Extended contact (over 6 hours) without use may cause the media to buckle while cooling.*

- Minimum recommended application temperature: +10 °C (+50 °F).
- Operating temperature range (outdoors): -20 °C to +60 °C (-4 °F to +140 °F).
- Adhesion to glass, steel, aluminium, PVC, melamine, etc. except grain substrates or substrates coated with acrylic paint.

*When applied to laminated monomeric or polymeric PVC films, the removable adhesives can become semi-permanent. The duration of application and the type of exposure may accelerate this phenomenon.*

- In the case of an already painted substrate, self-adhesive media must only be applied to undamaged original paintwork. If the paintwork is not original and/or damaged, the application and the removal are at the judgement and risk of the installer.

**OPERATING RECOMMENDATIONS:**

- The surface finish of your printing may be modified/improved/protected by a judicious choice of laminating films V700 or V650. For UV printing, protect with the laminating film VCR650.

**STORAGE:**

- Shelf life (before application):

The shelf life of this film is 1 year when stored unopened in its original packaging at a temperature ranging from 15 °C to 25 °C (+59 °F to +77 °F) with relative humidity between 30 % and 70 %.

**DURABILITY:** (Central European climate)

- Vertical outdoor exposure on flat surfaces:
  - Unprinted: 6 months depending on the substrate without significant traces of adhesive.
  - Printed and laminated: 12 months (if the print edges are sealed by a sealing varnish).
  - Printed: 3 months without significant traces of adhesive.

*To find the indicative durabilities of the films for any other exposure and geographical area, please refer to the "Conversion rules for indicative durabilities according to geographical area" chart available under Durability, on the "Professionals" pages on our site [www.hexis-graphics.com](http://www.hexis-graphics.com).*

**NOTES:**

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).