



DATA SHEET - DIGITAL PRINTING - MATT PAPER

PAP I 20JF

Fluorescent yellow, non-adhesive, 120-g/m² paper, suitable for standard solvent, eco-solvent, latex and UV inkjet printing.

FILM FEATURES:

Indicative values

- Thickness (µm): 124
- Weight (g/m²): 120

GENERAL PRINTER COMPATIBILITIES:

| | Solvent | Eco-solvent | Latex | UV |
|--------------------|----------------|--------------------|--------------|-----------|
| PAP I 20 JF | ✓ | ✓ | ✓ | ✓ |

USER'S INSTRUCTIONS:

- Store under printing conditions (temperature, hygrometry) a few days before printing.
- For indoor use.

STORAGE:

- Shelf life (before use):

The shelf life of this film is 1 year when stored upright in its original packaging in a dust-free environment at a temperature ranging from 15 °C to 25 °C (+59 °F to +77 °F) with relative humidity of 50 %.

In the case of partial use, replace the remaining roll in its original packaging.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application.

The measuring methods for the standards quoted above served as basis for the development of our own measuring methods which are available on request. Please feel free to contact us to get the latest instructions in use.

All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.