



## TECHNICAL DATA SHEET - VINYL WALL PAPER - PAPER BASE

# WALLPAPERS DIGIFORT® P300

Wall covering consisting of a vinyl-coated paper base. For solvent, eco-solvent, latex and UV inkjet printing. Structured / embossed surface appearance, "Dust" (PI3003) or "Mellow" finish (PI3004).

### **FILM FEATURES:**

#### Indicative values

- Total thickness of the product (µm): depends upon embossing / structure
- Total weight of the product (g/m<sup>2</sup>): 300
- Weight of the vinyl layer (g/m<sup>2</sup>): 210
- Weight of the paper substrate (g/m<sup>2</sup>): 90

### **GENERAL PRINTER COMPATIBILITIES:**

	<b>Solvent</b>	<b>Eco-solvent</b>	<b>Latex</b>	<b>UV</b>
<b>WALLPAPERS DIGIFORT® P300</b>	✓	✓	✓	✓

### **USER'S INSTRUCTIONS:**

- Touch-dry after less than 10 minutes depending on printer used.
- For any application, optimal drying time for the inks is 24 hours minimum.
- For indoor use.
- To be applied using a wall covering adhesive, such as PVA or similar, compatible with an application to:
  - porous and absorbent surfaces
  - or
  - non-absorbent surfaces, such as glass, plastic, metal or underlying wall covering, etc.
- The WALLPAPERS DIGIFORT® P300 are washable. Slightly soiled or dusty surfaces can be cleaned with a mild, non-abrasive, bleach-free detergent using a moistened, soft cloth or natural sponge. Dab the surface with the damp cloth / sponge (do not rub). Finally, rinse with a cloth / sponge soaked with clean water.

**RECOMMENDATIONS:**

- For further information on the application method of the WALLPAPERS DIGIFORT® P300 film, please refer to the Application Guide available on the "Professionals" pages on our website at [www.hexis-graphics.com](http://www.hexis-graphics.com).

**STORAGE:**

- Shelf life (before use):

The shelf life of this film is 1 year when stored upright in its original packaging in a dust-free environment at a temperature ranging from +15 °C to +25 °C (+59 °F to +77 °F) with relative humidity of 50 %.

**CERTIFICATIONS:**

- This product is B-s2, d0 classified according to the European standard EN13501-1: Fire classification of construction products and building elements (protocol no. 13854A).

**NOTES:**

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).